



ÉCLAIRAGE INTÉRIEUR
PLAFOND HAUT

UFO



SPÉCIFICATIONS

CODE DE PRODUIT	DESCRIPTION	WATTS	LUMENS	L / W	VOLTS	CCT	COUL.
DNA-2-UFO-100W-V3-5000-BLK	UFO 100W 100-347	100	13162	132	100-347	5000	BLK
DNA-2-UFO-150W-V3-5000-BLK	UFO 150W 100-347	150	19681	131	100-347	5000	BLK
DNA-2-UFO-200W-V3-5000-BLK	UFO 200W 100-347	200	26707	134	100-347	5000	BLK
DNA-2-UFO-240W-V3-5000-BLK	UFO 240W 100-347	240	31153	130	100-347	5000	BLK

CARACTÉRISTIQUES

- Indice de protection IP65 pour légère humidité
- Allumage immédiat
- Intensité réglable
- Fil et crochet pour installation inclus

AUSSI DISPONIBLES

- 2700K à 6500K
- 120-277V et 277-480V
- Couleur blanc

CERTIFICATIONS



FONCTIONNALITÉ



GARANTIE



LINÉAIRE



SPÉCIFICATIONS

CODE DE PRODUIT	DESCRIPTION	WATTS	LUMENS	L / W	VOLTS	CCT	COUL.
DNA-2-HBL2FT-110W-V3-5000-WHT	HB LINÉAIRE 110W 2FT	110	15706	143	100-347	5000	WHT
DNA-2-HBL2FT-165W-V3-5000-WHT	HB LINÉAIRE 165W 2FT	165	22981	139	100-347	5000	WHT
DNA-2-HBL4FT-220W-V3-5000-WHT	HB LINÉAIRE 220W 4FT	220	30847	140	100-347	5000	WHT
DNA-2-HBL4FT-300W-V3-5000-WHT	HB LINÉAIRE 300W 4FT	300	40917	136	100-347	5000	WHT
DNA-5-HBL2FT-95W-V1-5000-WHT	HB INÉAIRE 2FT 95W	95	12550	132	100-277	5000	WHT/BLK
DNA-5-HBL2FT-110W-V1-5000-WHT	HB LINÉAIRE 2FT 110W	110	15620	142	100-277	5000	WHT/BLK
DNA-5-HBL2FT-160W-V1-5000-WHT	HB LINÉAIRE 2FT 160W	160	21120	132	100-277	5000	WHT/BLK
DNA-5-HBL4FT-225W-V1-5000-WHT	HB LINÉAIRE 4FT 225W	225	29700	132	100-277	5000	WHT/BLK
DNA-5-HBL4FT-320W-V1-5000-WHT	HB LINÉAIRE 4FT 320W	320	42240	132	100-277	5000	WHT/BLK

CARACTÉRISTIQUES

- Très haute efficacité
- Intensité réglable
- Installation suspendu

AUSSI DISPONIBLES

- 120-277V et 277-480V
- 3000 à 6500K
- Blanc ou noir

CERTIFICATIONS



GARANTIE



FONCTIONNALITÉ

